



GANTRAIL®

The Sealing Strip

Making Good Things Better

The Sealing Strip

Alutherm

The finger-thick, prefabricated sealing strip made from a special clay-mixture guarantees an easy, secure and tight closing of moulds around rail.

One weld requires a maximum of 0.9kg (=10 prefabricated strips) of the sealing material, which is incorporated into the mould-cardbox.

For easy handling by a 2-person welding team, the strips are surrounded by one vacuum-closed, airtight bag with 2 small packs each holding 5 strips.

Thus, the sealing-strips are available on site without further logistical arrangement in all kinds of weather.

Due to the softness of the prefabricated cords, the sealing material fits easily into the tightening-grooves of the moulds. During preheating the material becomes a hard, reliable and tight gasket.

Eliminates improper weldings resulting from:



- gas-bubbles caused by wet sand,
- sand-enclosures,
- bubbles of incorporated sand,
- pores at the welding-bulge and
- leakage caused by dry sand.

Using the sealing strips eliminates the need for sack-loads of sand, collecting dishes or other ballast protections and/or layers.



Old-style operation!



Gantry Railing Limited

Sudmeadow Road, Hempsted, Gloucester GL2 5HG, England
Tel: #44 1452 300688 · Fax: #44 1452 300198
e-mail: info@gantry.co.uk · www.gantry.co.uk

Gantrail (Middle East) Limited

PO Box 61428, Jebel Ali Free Zone, Dubai, United Arab Emirates
Tel: #971 4 8812 935 · Fax: #971 4 8812 936
e-mail: gantrail@emirates.net.ae



Certificate no. 5180

NOT FOR DISTRIBUTION IN NORTH AMERICA AND CANADA